

Network Device Product Family

C1200

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C1200-8T-E-2G	GLC-TE	TMGBU	10/100/ 1000 Mbps	SFP	100m	Cat5e/6A	Copper	RJ-45	Copper	-5 to 85C		Please see datasheet and installation guide for minimum software release and configurati on support information .	—
Network Device Notes for above line : • Supports 1000BAST-T data rate only.													
C1200-8T-E-2G	GLC-BX-D	TMG	1 Gbps	SFP	10km	Single-strand Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configurati on support information .	—
C1200-8T-E-2G	GLC-BX-U	TMG	1 Gbps	SFP	10km	Single-strand Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configurati on support information .	—
C1200-8T-E-2G	GLC-SX-MMD	TMG	1 Gbps	SFP	1000m	Duplex Fiber	MMF	LC (PC or UPC)	Optic	-5 to 85C	Y	Please see datasheet and installation guide for minimum software release and configurati on support information .	—
Transceiver Notes for above line : • FDDI: 220m; OM1: 275m; OM2: 550m; OM3, OM4/OM5: 1000m													
C1200-8T-E-2G	GLC-LH-SMD	TMG	1 Gbps	SFP	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	-5 to 85C	Y	Please see datasheet and installation guide for minimum software release and configurati on support information .	—
Transceiver Notes for above line : • GLC-LH-SMD can be used on MMF with a maximum reach of 550m • LC mode-conditioning cable required for MMF applications													

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C1200-8T-E-2G	MGBSX1	SBTGBU	1 Gbps	SFP		Duplex Fiber	MMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-8T-E-2G	MGBLH1	SBTGBU	1 Gbps	SFP	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-8T-E-2G	MGBLX1	SBTGBU	1 Gbps	SFP	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-8T-E-2G	MGBT1	SBTGBU	1 Gbps	SFP	100m	Cat5e/6A	Copper	RJ-45	Optic	0 to 70C		Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-8P-E-2G	GLC-TE	TMGBU	10/100/1000 Mbps	SFP	100m	Cat5e/6A	Copper	RJ-45	Copper	-5 to 85C		Please see datasheet and installation guide for minimum software release and configuration support information .	—

Network Device Notes for above line :

- Supports 1000BAST-T data rate only.

C1200-8P-E-2G	GLC-BX-D	TMG	1 Gbps	SFP	10km	Single-strand Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-8P-E-2G	GLC-BX-U	TMG	1 Gbps	SFP	10km	Single-strand Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-8P-E-2G	GLC-SX-MMD	TMG	1 Gbps	SFP	1000m	Duplex Fiber	MMF	LC (PC or UPC)	Optic	-5 to 85C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—

Transceiver Notes for above line :

- FDDI: 220m; OM1: 275m; OM2: 550m; OM3, OM4/OM5: 1000m

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C1200-8P-E-2G	GLC-LH-SMD	TMG	1 Gbps	SFP	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	-5 to 85C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
Transceiver Notes for above line : • GLC-LH-SMD can be used on MMF with a maximum reach of 550m • LC mode-conditioning cable required for MMF applications													
C1200-8P-E-2G	MGBSX1	SBTGBU	1 Gbps	SFP		Duplex Fiber	MMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-8P-E-2G	MGBLH1	SBTGBU	1 Gbps	SFP	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-8P-E-2G	MGBLX1	SBTGBU	1 Gbps	SFP	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-8P-E-2G	MGBT1	SBTGBU	1 Gbps	SFP	100m	Cat5e/6A	Copper	RJ-45	Optic	0 to 70C		Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-8FP-E-2G	GLC-TE	TMGBU	10/100/1000 Mbps	SFP	100m	Cat5e/6A	Copper	RJ-45	Copper	-5 to 85C		Please see datasheet and installation guide for minimum software release and configuration support information .	—
Network Device Notes for above line : • Supports 1000BAST-T data rate only.													
C1200-8FP-E-2G	GLC-BX-D	TMG	1 Gbps	SFP	10km	Single-strand Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-8FP-E-2G	GLC-BX-U	TMG	1 Gbps	SFP	10km	Single-strand Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C1200-8FP-E-2G	GLC-SX-MMD	TMG	1 Gbps	SFP	1000m	Duplex Fiber	MMF	LC (PC or UPC)	Optic	-5 to 85C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
Transceiver Notes for above line : • FDDI: 220m; OM1: 275m; OM2: 550m; OM3, OM4/OM5: 1000m													
C1200-8FP-E-2G	GLC-LH-SMD	TMG	1 Gbps	SFP	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	-5 to 85C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
Transceiver Notes for above line : • GLC-LH-SMD can be used on MMF with a maximum reach of 550m • LC mode-conditioning cable required for MMF applications													
C1200-8FP-E-2G	MGBSX1	SBTGBU	1 Gbps	SFP		Duplex Fiber	MMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-8FP-E-2G	MGBLH1	SBTGBU	1 Gbps	SFP	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-8FP-E-2G	MGBLX1	SBTGBU	1 Gbps	SFP	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-8FP-E-2G	MGBT1	SBTGBU	1 Gbps	SFP	100m	Cat5e/6A	Copper	RJ-45	Optic	0 to 70C		Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-16T-2G	GLC-TE	TMGBU	10/100/1000 Mbps	SFP	100m	Cat5e/6A	Copper	RJ-45	Copper	-5 to 85C		Please see datasheet and installation guide for minimum software release and configuration support information .	—
Network Device Notes for above line : • Supports 1000BAST-T data rate only.													
C1200-16T-2G	GLC-BX-D	TMG	1 Gbps	SFP	10km	Single-strand Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C1200-16T-2G	GLC-BX-U	TMG	1 Gbps	SFP	10km	Single-strand Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configurati on support information .	—
C1200-16T-2G	GLC-SX-MMD	TMG	1 Gbps	SFP	1000m	Duplex Fiber	MMF	LC (PC or UPC)	Optic	-5 to 85C	Y	Please see datasheet and installation guide for minimum software release and configurati on support information .	—
Transceiver Notes for above line : • FDDI: 220m; OM1: 275m; OM2: 550m; OM3, OM4/OM5: 1000m													
C1200-16T-2G	GLC-LH-SMD	TMG	1 Gbps	SFP	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	-5 to 85C	Y	Please see datasheet and installation guide for minimum software release and configurati on support information .	—
Transceiver Notes for above line : • GLC-LH-SMD can be used on MMF with a maximum reach of 550m • LC mode-conditioning cable required for MMF applications													
C1200-16T-2G	MGBSX1	SBTGBU	1 Gbps	SFP		Duplex Fiber	MMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configurati on support information .	—
C1200-16T-2G	MGBLH1	SBTGBU	1 Gbps	SFP	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configurati on support information .	—
C1200-16T-2G	MGBLX1	SBTGBU	1 Gbps	SFP	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configurati on support information .	—
C1200-16T-2G	MGBT1	SBTGBU	1 Gbps	SFP	100m	Cat5e/6A	Copper	RJ-45	Optic	0 to 70C		Please see datasheet and installation guide for minimum software release and configurati on support information .	—
C1200-16P-2G	GLC-TE	TMGBU	10/100/ 1000 Mbps	SFP	100m	Cat5e/6A	Copper	RJ-45	Copper	-5 to 85C		Please see datasheet and installation guide for minimum software release and configurati on support information .	—
Network Device Notes for above line : • Supports 1000BASE-T data rate only.													

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C1200-16P-2G	GLC-BX-D	TMG	1 Gbps	SFP	10km	Single-strand Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-16P-2G	GLC-BX-U	TMG	1 Gbps	SFP	10km	Single-strand Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-16P-2G	GLC-SX-MMD	TMG	1 Gbps	SFP	1000m	Duplex Fiber	MMF	LC (PC or UPC)	Optic	-5 to 85C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
Transceiver Notes for above line : • FDDI: 220m; OM1: 275m; OM2: 550m; OM3, OM4/OM5: 1000m													
C1200-16P-2G	GLC-LH-SMD	TMG	1 Gbps	SFP	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	-5 to 85C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
Transceiver Notes for above line : • GLC-LH-SMD can be used on MMF with a maximum reach of 550m • LC mode-conditioning cable required for MMF applications													
C1200-16P-2G	MGBSX1	SBTGBU	1 Gbps	SFP		Duplex Fiber	MMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-16P-2G	MGBLH1	SBTGBU	1 Gbps	SFP	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-16P-2G	MGBLX1	SBTGBU	1 Gbps	SFP	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-16P-2G	MGBT1	SBTGBU	1 Gbps	SFP	100m	Cat5e/6A	Copper	RJ-45	Optic	0 to 70C		Please see datasheet and installation guide for minimum software release and configuration support information .	—

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C1200-24T-4G	GLC-TE	TMGBU	10/100/1000 Mbps	SFP	100m	Cat5e/6A	Copper	RJ-45	Copper	-5 to 85C		Please see datasheet and installation guide for minimum software release and configuration support information .	—
Network Device Notes for above line : • Supports 1000BAST-T data rate only.													
C1200-24T-4G	GLC-BX-D	TMG	1 Gbps	SFP	10km	Single-strand Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-24T-4G	GLC-BX-U	TMG	1 Gbps	SFP	10km	Single-strand Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-24T-4G	GLC-SX-MMD	TMG	1 Gbps	SFP	1000m	Duplex Fiber	MMF	LC (PC or UPC)	Optic	-5 to 85C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
Transceiver Notes for above line : • FDDI: 220m; OM1: 275m; OM2: 550m; OM3, OM4/OM5: 1000m													
C1200-24T-4G	GLC-LH-SMD	TMG	1 Gbps	SFP	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	-5 to 85C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
Transceiver Notes for above line : • GLC-LH-SMD can be used on MMF with a maximum reach of 550m • LC mode-conditioning cable required for MMF applications													
C1200-24T-4G	MGBSX1	SBTGBU	1 Gbps	SFP		Duplex Fiber	MMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-24T-4G	MGBLH1	SBTGBU	1 Gbps	SFP	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-24T-4G	MGBLX1	SBTGBU	1 Gbps	SFP	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C1200-24T-4G	MGBT1	SBTGBU	1 Gbps	SFP	100m	Cat5e/6A	Copper	RJ-45	Optic	0 to 70C		Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-24P-4G	GLC-TE	TMGBU	10/100/1000 Mbps	SFP	100m	Cat5e/6A	Copper	RJ-45	Copper	-5 to 85C		Please see datasheet and installation guide for minimum software release and configuration support information .	—
Network Device Notes for above line : • Supports 1000BAST-T data rate only.													
C1200-24P-4G	GLC-BX-D	TMG	1 Gbps	SFP	10km	Single-strand Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-24P-4G	GLC-BX-U	TMG	1 Gbps	SFP	10km	Single-strand Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-24P-4G	GLC-SX-MMD	TMG	1 Gbps	SFP	1000m	Duplex Fiber	MMF	LC (PC or UPC)	Optic	-5 to 85C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
Transceiver Notes for above line : • FDDI: 220m; OM1: 275m; OM2: 550m; OM3, OM4/OM5: 1000m													
C1200-24P-4G	GLC-LH-SMD	TMG	1 Gbps	SFP	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	-5 to 85C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
Transceiver Notes for above line : • GLC-LH-SMD can be used on MMF with a maximum reach of 550m • LC mode-conditioning cable required for MMF applications													
C1200-24P-4G	MGBSX1	SBTGBU	1 Gbps	SFP		Duplex Fiber	MMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-24P-4G	MGBLH1	SBTGBU	1 Gbps	SFP	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C1200-24P-4G	MGBLX1	SBTGBU	1 Gbps	SFP	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-24P-4G	MGBT1	SBTGBU	1 Gbps	SFP	100m	Cat5e/6A	Copper	RJ-45	Optic	0 to 70C		Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-24FP-4G	GLC-TE	TMGBU	10/100/1000 Mbps	SFP	100m	Cat5e/6A	Copper	RJ-45	Copper	-5 to 85C		Please see datasheet and installation guide for minimum software release and configuration support information .	—
Network Device Notes for above line : • Supports 1000BAST-T data rate only.													
C1200-24FP-4G	GLC-BX-D	TMG	1 Gbps	SFP	10km	Single-strand Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-24FP-4G	GLC-BX-U	TMG	1 Gbps	SFP	10km	Single-strand Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-24FP-4G	GLC-SX-MMD	TMG	1 Gbps	SFP	1000m	Duplex Fiber	MMF	LC (PC or UPC)	Optic	-5 to 85C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
Transceiver Notes for above line : • FDDI: 220m; OM1: 275m; OM2: 550m; OM3, OM4/OM5: 1000m													
C1200-24FP-4G	GLC-LH-SMD	TMG	1 Gbps	SFP	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	-5 to 85C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
Transceiver Notes for above line : • GLC-LH-SMD can be used on MMF with a maximum reach of 550m • LC mode-conditioning cable required for MMF applications													
C1200-24FP-4G	MGBSX1	SBTGBU	1 Gbps	SFP		Duplex Fiber	MMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C1200-24FP-4G	MGBLH1	SBTGBU	1 Gbps	SFP	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-24FP-4G	MGBLX1	SBTGBU	1 Gbps	SFP	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-24FP-4G	MGBT1	SBTGBU	1 Gbps	SFP	100m	Cat5e/6A	Copper	RJ-45	Optic	0 to 70C		Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-48T-4G	GLC-TE	TMGBU	10/100/1000 Mbps	SFP	100m	Cat5e/6A	Copper	RJ-45	Copper	-5 to 85C		Please see datasheet and installation guide for minimum software release and configuration support information .	—

Network Device Notes for above line :

- Supports 1000BAST-T data rate only.

C1200-48T-4G	GLC-BX-D	TMG	1 Gbps	SFP	10km	Single-strand Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-48T-4G	GLC-BX-U	TMG	1 Gbps	SFP	10km	Single-strand Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-48T-4G	GLC-SX-MMD	TMG	1 Gbps	SFP	1000m	Duplex Fiber	MMF	LC (PC or UPC)	Optic	-5 to 85C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—

Transceiver Notes for above line :

- FDDI: 220m; OM1: 275m; OM2: 550m; OM3, OM4/OM5: 1000m

C1200-48T-4G	GLC-LH-SMD	TMG	1 Gbps	SFP	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	-5 to 85C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
--------------	------------	-----	--------	-----	------	--------------	-----	----------------	-------	-----------	---	--	---

Transceiver Notes for above line :

- GLC-LH-SMD can be used on MMF with a maximum reach of 550m
- LC mode-conditioning cable required for MMF applications

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C1200-48T-4G	MGBSX1	SBTGBU	1 Gbps	SFP		Duplex Fiber	MMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-48T-4G	MGBLH1	SBTGBU	1 Gbps	SFP	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-48T-4G	MGBLX1	SBTGBU	1 Gbps	SFP	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-48T-4G	MGBT1	SBTGBU	1 Gbps	SFP	100m	Cat5e/6A	Copper	RJ-45	Optic	0 to 70C		Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-48P-4G	GLC-TE	TMGBU	10/100/1000 Mbps	SFP	100m	Cat5e/6A	Copper	RJ-45	Copper	-5 to 85C		Please see datasheet and installation guide for minimum software release and configuration support information .	—

Network Device Notes for above line :

- Supports 1000BAST-T data rate only.

C1200-48P-4G	GLC-BX-D	TMG	1 Gbps	SFP	10km	Single-strand Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-48P-4G	GLC-BX-U	TMG	1 Gbps	SFP	10km	Single-strand Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-48P-4G	GLC-SX-MMD	TMG	1 Gbps	SFP	1000m	Duplex Fiber	MMF	LC (PC or UPC)	Optic	-5 to 85C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—

Transceiver Notes for above line :

- FDDI: 220m; OM1: 275m; OM2: 550m; OM3, OM4/OM5: 1000m

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C1200-48P-4G	GLC-LH-SMD	TMG	1 Gbps	SFP	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	-5 to 85C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
Transceiver Notes for above line : • GLC-LH-SMD can be used on MMF with a maximum reach of 550m • LC mode-conditioning cable required for MMF applications													
C1200-48P-4G	MGBSX1	SBTGBU	1 Gbps	SFP		Duplex Fiber	MMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-48P-4G	MGBLH1	SBTGBU	1 Gbps	SFP	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-48P-4G	MGBLX1	SBTGBU	1 Gbps	SFP	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-48P-4G	MGBT1	SBTGBU	1 Gbps	SFP	100m	Cat5e/6A	Copper	RJ-45	Optic	0 to 70C		Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-24T-4X	SFP-10G-SR	TMG	10 Gbps	SFP+	400m	Duplex Fiber	MMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
Transceiver Notes for above line : • FDDI: 26m; OM1: 33m; OM2: 82m; OM3: 300m; OM4/OM5: 400m													
C1200-24T-4X	SFP-10G-SR-S	TMG	10 Gbps	SFP+	400m	Duplex Fiber	MMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
Transceiver Notes for above line : • FDDI: 26m; OM1: 33m; OM2: 82m; OM3: 300m; OM4/OM5: 400m													
C1200-24T-4X	SFP-10G-LR	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C1200-24T-4X	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-24T-4X	SFP-H10GB-CU1M	TMG	10 Gbps	SFP+	1m	Preterminated cable	DAC	N/A	Cable	0 to 70C		Please see datasheet and installation guide for minimum software release and configuration support information .	—
Transceiver Notes for above line : • Only Version -02 and later of this DAC is supported													
C1200-24T-4X	SFP-H10GB-CU3M	TMG	10 Gbps	SFP+	3m	Preterminated cable	DAC	N/A	Cable	0 to 70C		Please see datasheet and installation guide for minimum software release and configuration support information .	—
Transceiver Notes for above line : • Only Version -02 and later of this DAC is supported													
C1200-24T-4X	SFP-H10GB-CU5M	TMG	10 Gbps	SFP+	5m	Preterminated cable	DAC	N/A	Cable	0 to 70C		Please see datasheet and installation guide for minimum software release and configuration support information .	—
Transceiver Notes for above line : • Only Version -02 and later of this DAC is supported													
C1200-24T-4X	GLC-TE	TMGBU	10/100/1000 Mbps	SFP	100m	Cat5e/6A	Copper	RJ-45	Copper	-5 to 85C		Please see datasheet and installation guide for minimum software release and configuration support information .	—
Network Device Notes for above line : • Supports 1000BAST-T data rate only.													
C1200-24T-4X	GLC-BX-D	TMG	1 Gbps	SFP	10km	Single-strand Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-24T-4X	GLC-BX-U	TMG	1 Gbps	SFP	10km	Single-strand Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C1200-24T-4X	GLC-SX-MMD	TMG	1 Gbps	SFP	1000m	Duplex Fiber	MMF	LC (PC or UPC)	Optic	-5 to 85C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
Transceiver Notes for above line : • FDDI: 220m; OM1: 275m; OM2: 550m; OM3, OM4/OM5: 1000m													
C1200-24T-4X	GLC-LH-SMD	TMG	1 Gbps	SFP	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	-5 to 85C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
Transceiver Notes for above line : • GLC-LH-SMD can be used on MMF with a maximum reach of 550m • LC mode-conditioning cable required for MMF applications													
C1200-24T-4X	MGBSX1	SBTGBU	1 Gbps	SFP		Duplex Fiber	MMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-24T-4X	MGBLH1	SBTGBU	1 Gbps	SFP	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-24T-4X	MGBLX1	SBTGBU	1 Gbps	SFP	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-24T-4X	MGBT1	SBTGBU	1 Gbps	SFP	100m	Cat5e/6A	Copper	RJ-45	Optic	0 to 70C		Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-24P-4X	SFP-10G-SR	TMG	10 Gbps	SFP+	400m	Duplex Fiber	MMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
Transceiver Notes for above line : • FDDI: 26m; OM1: 33m; OM2: 82m; OM3: 300m; OM4/OM5: 400m													
C1200-24P-4X	SFP-10G-SR-S	TMG	10 Gbps	SFP+	400m	Duplex Fiber	MMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
Transceiver Notes for above line : • FDDI: 26m; OM1: 33m; OM2: 82m; OM3: 300m; OM4/OM5: 400m													
C1200-24P-4X	SFP-10G-LR	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-24P-4X	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-24P-4X	SFP-H10GB-CU1M	TMG	10 Gbps	SFP+	1m	Preterminated cable	DAC	N/A	Cable	0 to 70C		Please see datasheet and installation guide for minimum software release and configuration support information .	—
Transceiver Notes for above line : • Only Version -02 and later of this DAC is supported													
C1200-24P-4X	SFP-H10GB-CU3M	TMG	10 Gbps	SFP+	3m	Preterminated cable	DAC	N/A	Cable	0 to 70C		Please see datasheet and installation guide for minimum software release and configuration support information .	—
Transceiver Notes for above line : • Only Version -02 and later of this DAC is supported													
C1200-24P-4X	SFP-H10GB-CU5M	TMG	10 Gbps	SFP+	5m	Preterminated cable	DAC	N/A	Cable	0 to 70C		Please see datasheet and installation guide for minimum software release and configuration support information .	—
Transceiver Notes for above line : • Only Version -02 and later of this DAC is supported													
C1200-24P-4X	GLC-TE	TMGBU	10/100/1000 Mbps	SFP	100m	Cat5e/6A	Copper	RJ-45	Copper	-5 to 85C		Please see datasheet and installation guide for minimum software release and configuration support information .	—
Network Device Notes for above line : • Supports 1000BAST-T data rate only.													
C1200-24P-4X	GLC-BX-D	TMG	1 Gbps	SFP	10km	Single-strand Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C1200-24P-4X	GLC-BX-U	TMG	1 Gbps	SFP	10km	Single-strand Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configurati on support information .	—
C1200-24P-4X	GLC-SX-MMD	TMG	1 Gbps	SFP	1000m	Duplex Fiber	MMF	LC (PC or UPC)	Optic	-5 to 85C	Y	Please see datasheet and installation guide for minimum software release and configurati on support information .	—
Transceiver Notes for above line : • FDDI: 220m; OM1: 275m; OM2: 550m; OM3, OM4/OM5: 1000m													
C1200-24P-4X	GLC-LH-SMD	TMG	1 Gbps	SFP	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	-5 to 85C	Y	Please see datasheet and installation guide for minimum software release and configurati on support information .	—
Transceiver Notes for above line : • GLC-LH-SMD can be used on MMF with a maximum reach of 550m • LC mode-conditioning cable required for MMF applications													
C1200-24P-4X	MGBSX1	SBTGBU	1 Gbps	SFP		Duplex Fiber	MMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configurati on support information .	—
C1200-24P-4X	MGBLH1	SBTGBU	1 Gbps	SFP	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configurati on support information .	—
C1200-24P-4X	MGBLX1	SBTGBU	1 Gbps	SFP	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configurati on support information .	—
C1200-24P-4X	MGBT1	SBTGBU	1 Gbps	SFP	100m	Cat5e/6A	Copper	RJ-45	Optic	0 to 70C		Please see datasheet and installation guide for minimum software release and configurati on support information .	—
C1200-24FP-4X	SFP-10G-SR	TMG	10 Gbps	SFP+	400m	Duplex Fiber	MMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configurati on support information .	—
Transceiver Notes for above line : • FDDI: 26m; OM1: 33m; OM2: 82m; OM3: 300m; OM4/OM5: 400m													

Network Device Product ID	Transciever Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C1200-24FP-4X	SFP-10G-SR-S	TMG	10 Gbps	SFP+	400m	Duplex Fiber	MMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configurati on support information .	—
Transceiver Notes for above line : • FDDI: 26m; OM1: 33m; OM2: 82m; OM3: 300m; OM4/OM5: 400m													
C1200-24FP-4X	SFP-10G-LR	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configurati on support information .	—
C1200-24FP-4X	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configurati on support information .	—
C1200-24FP-4X	SFP-H10GB- CU1M	TMG	10 Gbps	SFP+	1m	Preterminated cable	DAC	N/A	Cable	0 to 70C		Please see datasheet and installation guide for minimum software release and configurati on support information .	—
Transceiver Notes for above line : • Only Version -02 and later of this DAC is supported													
C1200-24FP-4X	SFP-H10GB- CU3M	TMG	10 Gbps	SFP+	3m	Preterminated cable	DAC	N/A	Cable	0 to 70C		Please see datasheet and installation guide for minimum software release and configurati on support information .	—
Transceiver Notes for above line : • Only Version -02 and later of this DAC is supported													
C1200-24FP-4X	SFP-H10GB- CU5M	TMG	10 Gbps	SFP+	5m	Preterminated cable	DAC	N/A	Cable	0 to 70C		Please see datasheet and installation guide for minimum software release and configurati on support information .	—
Transceiver Notes for above line : • Only Version -02 and later of this DAC is supported													
C1200-24FP-4X	GLC-TE	TMGBU	10/100/ 1000 Mbps	SFP	100m	Cat5e/6A	Copper	RJ-45	Copper	-5 to 85C		Please see datasheet and installation guide for minimum software release and configurati on support information .	—
Network Device Notes for above line : • Supports 1000BAST-T data rate only.													

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C1200-24FP-4X	GLC-BX-D	TMG	1 Gbps	SFP	10km	Single-strand Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-24FP-4X	GLC-BX-U	TMG	1 Gbps	SFP	10km	Single-strand Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-24FP-4X	GLC-SX-MMD	TMG	1 Gbps	SFP	1000m	Duplex Fiber	MMF	LC (PC or UPC)	Optic	-5 to 85C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
Transceiver Notes for above line : • FDDI: 220m; OM1: 275m; OM2: 550m; OM3, OM4/OM5: 1000m													
C1200-24FP-4X	GLC-LH-SMD	TMG	1 Gbps	SFP	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	-5 to 85C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
Transceiver Notes for above line : • GLC-LH-SMD can be used on MMF with a maximum reach of 550m • LC mode-conditioning cable required for MMF applications													
C1200-24FP-4X	MGBSX1	SBTGBU	1 Gbps	SFP		Duplex Fiber	MMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-24FP-4X	MGBLH1	SBTGBU	1 Gbps	SFP	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-24FP-4X	MGBLX1	SBTGBU	1 Gbps	SFP	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-24FP-4X	MGBT1	SBTGBU	1 Gbps	SFP	100m	Cat5e/6A	Copper	RJ-45	Optic	0 to 70C		Please see datasheet and installation guide for minimum software release and configuration support information .	—

Network Device Product ID	Transciever Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C1200-48T-4X	SFP-10G-SR	TMG	10 Gbps	SFP+	400m	Duplex Fiber	MMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configurati on support information .	—
Transceiver Notes for above line : • FDDI: 26m; OM1: 33m; OM2: 82m; OM3: 300m; OM4/OM5: 400m													
C1200-48T-4X	SFP-10G-SR-S	TMG	10 Gbps	SFP+	400m	Duplex Fiber	MMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configurati on support information .	—
Transceiver Notes for above line : • FDDI: 26m; OM1: 33m; OM2: 82m; OM3: 300m; OM4/OM5: 400m													
C1200-48T-4X	SFP-10G-LR	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configurati on support information .	—
C1200-48T-4X	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configurati on support information .	—
C1200-48T-4X	SFP-H10GB- CU1M	TMG	10 Gbps	SFP+	1m	Preterminated cable	DAC	N/A	Cable	0 to 70C		Please see datasheet and installation guide for minimum software release and configurati on support information .	—
Transceiver Notes for above line : • Only Version -02 and later of this DAC is supported													
C1200-48T-4X	SFP-H10GB- CU3M	TMG	10 Gbps	SFP+	3m	Preterminated cable	DAC	N/A	Cable	0 to 70C		Please see datasheet and installation guide for minimum software release and configurati on support information .	—
Transceiver Notes for above line : • Only Version -02 and later of this DAC is supported													
C1200-48T-4X	SFP-H10GB- CU5M	TMG	10 Gbps	SFP+	5m	Preterminated cable	DAC	N/A	Cable	0 to 70C		Please see datasheet and installation guide for minimum software release and configurati on support information .	—
Transceiver Notes for above line : • Only Version -02 and later of this DAC is supported													

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C1200-48T-4X	GLC-TE	TMGBU	10/100/1000 Mbps	SFP	100m	Cat5e/6A	Copper	RJ-45	Copper	-5 to 85C		Please see datasheet and installation guide for minimum software release and configuration support information .	—
Network Device Notes for above line : • Supports 1000BAST-T data rate only.													
C1200-48T-4X	GLC-BX-D	TMG	1 Gbps	SFP	10km	Single-strand Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-48T-4X	GLC-BX-U	TMG	1 Gbps	SFP	10km	Single-strand Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-48T-4X	GLC-SX-MMD	TMG	1 Gbps	SFP	1000m	Duplex Fiber	MMF	LC (PC or UPC)	Optic	-5 to 85C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
Transceiver Notes for above line : • FDDI: 220m; OM1: 275m; OM2: 550m; OM3, OM4/OM5: 1000m													
C1200-48T-4X	GLC-LH-SMD	TMG	1 Gbps	SFP	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	-5 to 85C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
Transceiver Notes for above line : • GLC-LH-SMD can be used on MMF with a maximum reach of 550m • LC mode-conditioning cable required for MMF applications													
C1200-48T-4X	MGBSX1	SBTGBU	1 Gbps	SFP		Duplex Fiber	MMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-48T-4X	MGBLH1	SBTGBU	1 Gbps	SFP	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-48T-4X	MGBLX1	SBTGBU	1 Gbps	SFP	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C1200-48T-4X	MGBT1	SBTGBU	1 Gbps	SFP	100m	Cat5e/6A	Copper	RJ-45	Optic	0 to 70C		Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-48P-4X	SFP-10G-SR	TMG	10 Gbps	SFP+	400m	Duplex Fiber	MMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
Transceiver Notes for above line : • FDDI: 26m; OM1: 33m; OM2: 82m; OM3: 300m; OM4/OM5: 400m													
C1200-48P-4X	SFP-10G-SR-S	TMG	10 Gbps	SFP+	400m	Duplex Fiber	MMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
Transceiver Notes for above line : • FDDI: 26m; OM1: 33m; OM2: 82m; OM3: 300m; OM4/OM5: 400m													
C1200-48P-4X	SFP-10G-LR	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-48P-4X	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-48P-4X	SFP-H10GB-CU1M	TMG	10 Gbps	SFP+	1m	Preterminated cable	DAC	N/A	Cable	0 to 70C		Please see datasheet and installation guide for minimum software release and configuration support information .	—
Transceiver Notes for above line : • Only Version -02 and later of this DAC is supported													
C1200-48P-4X	SFP-H10GB-CU3M	TMG	10 Gbps	SFP+	3m	Preterminated cable	DAC	N/A	Cable	0 to 70C		Please see datasheet and installation guide for minimum software release and configuration support information .	—
Transceiver Notes for above line : • Only Version -02 and later of this DAC is supported													

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C1200-48P-4X	SFP-H10GB-CU5M	TMG	10 Gbps	SFP+	5m	Preterminated cable	DAC	N/A	Cable	0 to 70C		Please see datasheet and installation guide for minimum software release and configuration support information .	—
Transceiver Notes for above line : • Only Version -02 and later of this DAC is supported													
C1200-48P-4X	GLC-TE	TMGBU	10/100/1000 Mbps	SFP	100m	Cat5e/6A	Copper	RJ-45	Copper	-5 to 85C		Please see datasheet and installation guide for minimum software release and configuration support information .	—
Network Device Notes for above line : • Supports 1000BAST-T data rate only.													
C1200-48P-4X	GLC-BX-D	TMG	1 Gbps	SFP	10km	Single-strand Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-48P-4X	GLC-BX-U	TMG	1 Gbps	SFP	10km	Single-strand Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-48P-4X	GLC-SX-MMD	TMG	1 Gbps	SFP	1000m	Duplex Fiber	MMF	LC (PC or UPC)	Optic	-5 to 85C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
Transceiver Notes for above line : • FDDI: 220m; OM1: 275m; OM2: 550m; OM3, OM4/OM5: 1000m													
C1200-48P-4X	GLC-LH-SMD	TMG	1 Gbps	SFP	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	-5 to 85C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
Transceiver Notes for above line : • GLC-LH-SMD can be used on MMF with a maximum reach of 550m • LC mode-conditioning cable required for MMF applications													
C1200-48P-4X	MGBSX1	SBTGBU	1 Gbps	SFP		Duplex Fiber	MMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C1200-48P-4X	MGBLH1	SBTGBU	1 Gbps	SFP	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-48P-4X	MGBLX1	SBTGBU	1 Gbps	SFP	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-48P-4X	MGBT1	SBTGBU	1 Gbps	SFP	100m	Cat5e/6A	Copper	RJ-45	Optic	0 to 70C		Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-8FP-2G	GLC-TE	TMGBU	10/100/1000 Mbps	SFP	100m	Cat5e/6A	Copper	RJ-45	Copper	-5 to 85C		Please see datasheet and installation guide for minimum software release and configuration support information .	—

Network Device Notes for above line :

- Supports 1000BAST-T data rate only.

C1200-8FP-2G	GLC-BX-D	TMG	1 Gbps	SFP	10km	Single-strand Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-8FP-2G	GLC-BX-U	TMG	1 Gbps	SFP	10km	Single-strand Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
C1200-8FP-2G	GLC-SX-MMD	TMG	1 Gbps	SFP	1000m	Duplex Fiber	MMF	LC (PC or UPC)	Optic	-5 to 85C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—

Transceiver Notes for above line :

- FDDI: 220m; OM1: 275m; OM2: 550m; OM3, OM4/OM5: 1000m

C1200-8FP-2G	GLC-LH-SMD	TMG	1 Gbps	SFP	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	-5 to 85C	Y	Please see datasheet and installation guide for minimum software release and configuration support information .	—
--------------	------------	-----	--------	-----	------	--------------	-----	----------------	-------	-----------	---	--	---

Transceiver Notes for above line :

- GLC-LH-SMD can be used on MMF with a maximum reach of 550m
- LC mode-conditioning cable required for MMF applications

Network Device Product ID	Transciever Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
C1200-8FP-2G	MGBSX1	SBTGBU	1 Gbps	SFP		Duplex Fiber	MMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configurati on support information .	—
C1200-8FP-2G	MGBLH1	SBTGBU	1 Gbps	SFP	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configurati on support information .	—
C1200-8FP-2G	MGBLX1	SBTGBU	1 Gbps	SFP	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	Please see datasheet and installation guide for minimum software release and configurati on support information .	—
C1200-8FP-2G	MGBT1	SBTGBU	1 Gbps	SFP	100m	Cat5e/6A	Copper	RJ-45	Optic	0 to 70C		Please see datasheet and installation guide for minimum software release and configurati on support information .	—